





CHEKKIT® SMOKE Detector Tester

CHEKKIT® SMOKE is a hand-held functional tester of ionisation and optical smoke detectors. A quick one second spray from floor level provides a safe, reliable and economical method of testing.

- UL LISTED AND DETECTOR MANUFACTURER ENDORSED FORMULA
- EXTREMELY LOW COST PER TEST INDEX*
- FAST CLEARING TIME ULTRA LOW RESET INDEX*
- NON-FLAMMABLE
- NON-TOXIC
 - NO PHTHALATE ESTERS*
 - NO SILICON CONTENT*
 - OZONE FRIENDLY WITH NO CFCs
 - SENSOR SAFE DOES NOT DAMAGE PLASTIC CASING OR INTERNAL CIRCUITRY
 - MOST WIDELY USED DETECTOR TESTER FORMULA IN THE WORLD
 - DESIGNED AND MANUFACTURED BY WORLD'S GENUINE MARKET LEADER



* See website for details

www.detectortesters.com





CHEKKIT® SMOKE Detector Tester

Available in 35ml and 150ml aerosols

ALSO AVAILABLE FROM THE SAME MANUFACTURER

- Aerosol Dispensing Tools
 as recommended by detector manufacturers
- Professional Smoke Detector Testers with approved and listed dispenser
- Genuine Professional Heat Detectors suitable for fixed temperature, rate of rise and combined detectors
- CO Detector Testers
 with approved and listed dispenser
- Detector Removal Tools suitable for all leading makes and models of Detector
- Access Poles to enable detector maintenance up to 9 metres
- Complete Maintenance and Service Systems providing complete solutions in economical and convenient kit formats
- Smoke Detector Sensitivity Instruments
 to identify sensitivity drift and help ensure
 that smoke detector sensitivity is maintained
 within defined calibration parameters

HIGHEST STANDARDS

"The detectors shall be tested in place to ensure smoke entry into the sensing chamber and an alarm response. Testing with smoke or listed aerosol shall be permitted as one acceptable test method."

NFPA 72E, 8-2.4.1.1

"In the case of detectors (all types) tests must ensure that products of combustion are capable of passing unhindered from the protected area to the sensing chamber / elements of the detector and not simply test the ability of the detector to sample / verify the status of the atmosphere already in the sensing chamber."

BS5839 1: 2002; 45.3

"Point smoke detectors should be functionally tested by a method that confirms that smoke can enter the detector chamber and produce a fire alarm signal (e.g.: by use of apparatus that generates simulated smoke or suitable aerosols around the detector). It should be ensured that the material used does not cause damage to, or affect the subsequent performance of, the detector..."

BS5839 1: 2002; 45.4 (D)

"Since stimulus of the sensing element through introduction of the phenomena or surrogate phenomena which the detectors are designed to detect forms part of the test(s), use of a test button or a test magnet (for example) or compliance with 45(i) (confirmation of analogue values) does not satisfy the recommendations.."

BS5839 1: 2002 45.3 (Note 4)

CHEKKIT® SMOKE meets or exceeds all the relevant Fire Industry standards providing effective and consistent testing as well as the highest international standards on filling, labelling, safety and compatibility.



As our policy is one of continuous improvement, details of products described within this publication are subject to change without notice. All information provided here is believed to be correct at the time of going to press. Every effort has been made to ensure the accuracy of information which is provided in good faith but nothing contained herein is intended to incorporate any representation or warranty, either express or implied or to form the basis of any legal relations between the parties hereto, additional to or in lieu of such as may be applicable to a contract of sale or purchase.



No Climb Products Limited,

Edison House, 163 Dixons Hill Road, Welham Green, Hertfordshire. AL9 7JE. UK T: +44 (0) 1707 282760 F: +44 (0) 1707 282777 Email: sales@noclimb.com www.detectortesters.com